

Print Server with 2 USB and 1 Parallel Ports

Product Overview

The LevelOne FPS-1033 print server is an ideal network printing solution for small offices, home offices, schools and other businesses that require printer sharing over the same network. The FPS-1033 is a multi-port Fast Ethernet Print Server and provides network printer sharing for both USB and Parallel printers.

Multi Printer Support

The FPS-1033 Multi Port print server provides simultaneous connectivity to two USB and one Parallel printers. It supports the USB 2.0 standard for high-speed printing.

Multi OS and Network Printing Protocol Support

The FPS-1033 Multi Port Print Server supports Windows ME, 2000,2003 and XP operating systems as well as Mac OS 8.1 and higher and UNIX/Linux and Netware (Bindery/NDS). Network Print Protocol supported includes TCP/IP, IPX, NetBEUI, AppleTalk, LPR, SMB over TCP/IP and IPP for flexible use with different network clients connected to the same office network.



The LevelOne FPS-1033 is easily configurable using a Web Browser or Windows based configuration program included with the CD-ROM. The print server is easily managed through a Web based user interface and the firmware is upgradeable through TFTP, the windows set-up program or the Web based user interface.



FPS-1033

Key Features

- Multi-Port print server for network print sharing
- High-speed USB 2.0 interface
- Fast Ethernet network connectivity
- Fast Ethernet network connectivity

- Easy set-up wizard included
- Web based user interface
- Support multiple operating systems
- Support multiple network printing protocols

Technical Specification

Device Specifications

Standards Compliance

- IEEE 802.3 10Mbps Ethernet
- IEEE 802.3u 100Mpbs Fast Ethernet

Network Interface

- 1x 10/100Mbps Auto-sensing RJ-45 port
- 2x USB 2.0 Auto-sensing port
- 1x Parallel Printer Port (D-Type 25 pin female)
- DHCP Client

Operating System Support

- Windows ME, 2000, XP
- Mac OS 8.1 or higher
- UNIX/Linux
- NetWare (Bindery/NDS)

Network Print Protocol Support

 TCP/IP, IPX, NetBEUI, AppleTalk, LPR, SMB over TCP/IP, Internet Printing Protocol (IPP)

Software Upgradeable

- Web interface
- Windows-based Setup Program
- TFTP

Device Management

- Web-based user interface
- Windows-based Setup Program
- Telnet

Physical Specifications

LEDs

Power/Status, Link, Activity

Power Supply

5V, 2A

Dimension

180mm (L) x 100mm (W) x 35mm (H)

Weight

255g

Operating Temperature and Humidity

Operating: 0°C ~ 50°C @ 0% ~ 70% (non-condensing) Storage: -5°C ~ 65°C @ 0%~ 80% (non-condensing)


EMI Certifications

CE, FCC Class B





Product Diagram



Order Information

FPS-1033: Print Server w/ 2 USB and 1 Parallel Ports

Package Content

- -FPS-1033
- -Power Adapter
- -CD Manual/Driver/Utility
- -Quick Installation Guide

